

TITLE OF THE INVENTION

PROJECTION LENS SYSTEM AND PROJECTION IMAGE
DISPLAY APPARATUS USING THE SAME

BACKGROUND OF THE INVENTION

5 The present invention relates to a projection lens system and particularly to a projection lens system with a wide field angle which provides a bright image having an excellent focus performance even in the marginal area, uses an inexpensive glass material, and
10 has a short projection distance and a projection image display apparatus using the system which is excellent in cost performance.

 Recently, a television set as an image display apparatus for home use is proceeding to a larger
15 screen size as the wide aspect ratio increases. As an image display apparatus for home use, there are two types available such as a direct view type using a cathode ray tube and a so-called projection type for enlarging and projecting an image on a miniature
20 projection tube whose screen size is about 7 inch of diagonal on the screen by a projection lens system. However, due to restrictions to compactness and weight of a TV set, for a screen size of more than about 37 inch of diagonal, a projection image display apparatus
25 is mainly used.

At first, this projection image display apparatus was inferior to the direct view type in screen brightness and focus performance. However, recently, the performance of each of the components such as the projection lens system, screen, and projection tube is improved, so that both the screen brightness and focus performance are approaching those of the direct view type. In the performance improvement process of the projection image display apparatus, various arts have been developed in the projection lens system which is a key device. Firstly, at the first step of development, to obtain screen brightness equivalent to that of the direct view type or higher, as disclosed in U.S. Patent 4,682,862, reduction of the F-number has been tried by using many plastic aspherical lens elements.

Next, at the second step, a projection lens system for realizing improvement of screen brightness and improvement of focus performance at the same time has been developed. With respect to this projection lens system, as disclosed in Japanese Patent Application Laid-Open No. 3-137610, there is an example using a plastic aspherical lens and a doublet glass lens. As a result, in the current projection TV set, a projection lens system having an F-number of about $f/1.1$ is used

and both brightness and focus performance are improved on the whole screen.

At the third step, a projection lens system with a wide field angle by which a compact set dimension can be realized on account of the short projection distance has been developed mainly. A reference describing an actual art for realizing a projection lens system with a wide field angle without reducing the brightness and focus performance in the marginal area and an actual projection lens system is disclosed in Japanese Patent Application Laid-Open No. 4- 5608. Hereinafter, the art disclosed in this patent is referred to as a first prior art.

In this first prior art, by combining plastic aspherical lens elements and glass lens elements effectively in a projection lens system of six lens groups, the aforementioned problem is solved. Furthermore, the projection lens system is structured so that almost all the positive refractive power of the projection lens system is shared by the glass lenses and the plastic aspherical lens elements have little refractive power, so that the peculiar drift of the focus performance due to a temperature change is reduced even if the plastic aspherical lens elements are used is reduced.

In this first prior art, the profile of the fluorescent face of projection tube has a curvature so that it is convex on the electron gun side. As a result, the projection lens system is structured so
5 that the normal of the fluorescent face in the marginal area is in the direction of the entrance pupil of the projection lens system and can fetch more light fluxes in comparison with the case using a flat fluorescent face. Therefore, even if the field angle
10 is widened, a relative illuminance of a level which is almost no problem practically can be obtained in the marginal area.

The curvature of field is corrected by the lens element of the sixth lens group (hereinafter referred
15 to as sixth lens). However, if the fluorescent face of projection tube has a curvature so that it is convex on the electron gun side, the generation amount of curvature of field is reduced and the focus performance in the marginal area is improved.

20 Furthermore, a projection lens system with a wide field angle which realizes a more excellent focus performance without reducing the brightness in the marginal area and an actual art for realizing it are disclosed in U.S. Patent 5,272,540. Hereinafter, the
25 art is referred to as a second prior art.

In the second prior art, a projection lens system having a constitution of five groups by six elements is disclosed and the profile of the fluorescent face of projection tube which is an object is an aspherical profile which is convex on the electron gun side. And
5 has when the curvature of the profile in the marginal area is smaller than that in the neighborhood of the optical axis. By doing this, highly precise correction of the curvature of field and astigmatism are
10 compatible with each other and the satisfactory focus performance and the light amount which is practically sufficient are reserved in the marginal area of screen.

In this projection lens system, the lens element of the third lens group (hereinafter referred to as
15 third lens) sharing almost all refractive power of the overall lens system has a constitution that a concave lens of large dispersion glass and a convex lens of small dispersion glass are stuck together, and the chromatic aberration is corrected, and the large
20 aperture (the F-number is 0.96) and the high focus performance are compatible with each other.

Furthermore, it is structured that combination of the lens element of the first lens group (hereinafter referred to as first lens) and the lens element of the
25 second lens group (hereinafter referred to as second

lens) offsets the lowering of the focus performance generated by deformation and expansion of each lens element due to temperature change and humidity change which is an intrinsic problem when plastic lens
5 elements are used.

On the other hand, in a conventional projection lens system, as a lens barrel for assembling each lens element with high precision, a lens barrel having the constitution disclosed in, for example, Japanese
10 Utility Model Application Laid- Open No. 2-51478 is often used. The lens barrel of the prior art has an outer barrel and an inner barrel which is installed inside the outer barrel and can slide in the direction of optical axis of the lens without axial shift. The
15 inner barrel has a constitution that it can be divided into two parts longitudinally in the direction of diameter of the lens along the optical axis of the lens and it has slits for holding a plurality of lens elements at predetermined intervals with high
20 precision on its inner surface.

In the aforementioned projection lens system having a constitution of six lens groups of the first prior art, there are several problems to be solved.

The first problem is a problem caused by the lens
25 constitution. In the aforementioned projection lens

system, the third lens having negative refractive power is arranged on the screen side of the lens element of the fourth lens group (hereinafter referred to as fourth lens) sharing almost all the positive
5 refractive power of the overall lens system. The spherical aberration and coma aberration are corrected by the third lens.

Therefore, the location of the entrance pupil of the overall lens system moves to the screen side from
10 the center of the fourth lens. As a result, if an attempt is made to realize a wider field angle (reduction of the projection distance) in the aforementioned lens constitution, correction of the distortion and astigmatism becomes difficult.

15 Next, the second problem is a point that if an attempt is made to reduce the F-number or (increase the aperture ratio) of the projection lens system having this lens constitution and obtain a sufficient marginal light amount ratio, the apertures of the
20 first, second, and third lenses become larger and the production cost increases.

The share of correction of each lens group in aberration correction of the aforementioned projection lens system is shown below.

25 The first lens is a spherical lens element of a

meniscus profile having positive refractive power and corrects spherical aberration and coma aberration.

The second lens is a plastic aspherical lens element of a meniscus profile having weak positive
5 refractive power and corrects spherical aberration and coma aberration.

The third lens is a spherical lens element having a weak divergent action and corrects spherical aberration and coma aberration.

10 The fourth lens is a convex-convex glass spherical lens element having a strong convergent action.

Furthermore, the lens element of the fifth lens group (hereinafter referred to as fifth lens) is a plastic aspherical lens element of a meniscus profile
15 having weak positive refractive power and corrects astigmatism, distortion, and coma aberration.

The sixth lens has a constitution that it has a concave surface facing the screen side, has negative refractive power accompanied by a liquid coolant (A),
20 and corrects curvature of field.

Among them, the second lens and fifth lens are a plastic aspherical lens element and have a meniscus profile having weak positive refractive power respectively. This projection lens system of prior art
25 has a constitution that each plastic lens element has

little refractive power and the peculiar shift of the focus performance due to a temperature change when the plastic aspherical lens element is used is reduced.

There is a third problem imposed that as mentioned
5 above, in the projection lens system using the first prior art, the applicable lens profile of the plastic aspherical lens is limited to a specific profile and that the aberration correction cannot be attained sufficiently.

10 A fourth problem is also imposed that since four glass lens elements are included, the cost is increased.

Furthermore, the aspherical surface amount of the fifth lens is little, and the sixth lens is a glass
15 lens element, whereof the lens surface on the screen side is a spherical ~~surface~~, so that correction of astigmatism and correction of curvature of field are not compatible with each other.

Therefore, a fifth problem arises that correction
20 of astigmatism in the marginal area is difficult.

In the first prior art, it is a subject (of the design) to solve these problems.

A problem of the projection lens system having a constitution of five groups by six elements to be
25 solved in the second prior art is reduction in cost.

The two factors for an increase in the cost of the projection lens system are described below.

The first factor for an increase in cost is the profile of fluorescent face of the projection tube.

5 The main profile of fluorescent face of the projection tube is a spherical fluorescent face at present. When this projection lens system is applied, it is necessary to make the profile of fluorescent face aspherical and the projection tube is to be produced
10 under a special specification, so that it is a factor for an increase in the cost of the set.

The second factor for an increase in cost is that it is essential to use a doublet lens comprising a large dispersion concave lens with a large diameter
15 and a small dispersion convex lens with a large diameter which are stuck together for the third lens so as to realize a large aperture ratio (the F-number is 0.96) in this projection lens system and correct chromatic aberration satisfactorily.

20 Generally, the price of optical glass increases as the refractive index increases and as the dispersion decreases. In the second prior art, the optical glass used as a third lens of the projection lens system described in Embodiment 1 includes large dispersion
25 glass of SF11 and small dispersion glass of SK16. The

prices of these optical glass materials are more than
2 times as expensive as the price of SK5 which is a
typical one of optical glass used in the projection
lens system such that the price is 2.3 for SF11 and is
5 2.1 for SK16 (those glass names are abbreviations of
Schott, Ltd. and often used in this field).

On the other hand, a problem when the
aforementioned conventional lens barrel is used in the
projection lens system is that the air temperature in
10 the sealed space inside the lens barrel and the
temperature of the lens elements rise, and the heated
lens elements expands and deforms, and the focus
performance of the projection lens system is lowered
extremely.

15 As a result, it is a subject (of the design) to
suppress rising of the air temperature in the sealed
space inside the lens barrel and the temperature of
the lens elements and to prevent the lens elements
from expansion and deformation even if the heat
20 generated from an image generating source is high.

SUMMARY OF THE INVENTION

An object of the present invention is to solve the
problems of the projection lens system of the prior
art mentioned above and to provide a projection lens
25 system of a wide field angle which uses inexpensive

optical glass, has an excellent focus performance even in the marginal area even if the heat generated from an image generating source is high, obtains a bright image, and has a short projection distance and a
5 projection image display apparatus using the system which is excellent in cost performance.

To accomplish the above object, the projection lens system of the present invention uses technical means as described below.

10 Firstly, to solve the first and second problems of the first prior art, almost all the positive refractive power of the overall lens system is shared by the glass lens elements (hereinafter described as
15 glass power lens). In this case, a lens having negative refractive power is not arranged on the screen side of the lens group including the glass power lens but a plastic aspherical lens element having weak positive refractive power around the
20 optical axis is arranged there. As a result, the entrance pupil does not move to the screen side from the glass power lens, so that the first problem can be solved and a projection lens system with a wide field angle can be realized.

Furthermore, a light flux passing through the lens
25 group including the glass power lens diverges and

enters the lens groups positioned on the screen side, so that the aperture of each of lens groups can be made as small as possible and the second problem can be solved.

5 In the projection lens system of the present invention, to minimize the lowering of the focus performance due to temperature and humidity changes, the refractive power of the plastic aspherical lens element around the optical axis is reduced to 30% of
10 that of the glass power lens or less.

 The aberration depending on the aperture is corrected according to the profile of lens surface including aspherical system in the area (the marginal area of the lens element) apart from the optical axis.
15 The system is structured so that the drift of the local refractive power obtained according to the profile of lens surface including aspherical system in the marginal area of the lens due to temperature and humidity changes is offset by combining a plurality of
20 plastic aspherical lens elements. By doing this, the profile of lens element can be decided without affecting aberration correction restrictively and the third problem can be solved.

 Many plastic aspherical lens elements having a
25 lens surface including strong aspherical system can be

used by the aforementioned technical means, so that the number of glass lens elements can be reduced and the fourth problem can be solved.

5 To solve the fifth problem, a lens element having negative refractive power with the concave surface facing the screen side is arranged in the location closest to the projection tube which is an image light source, and the lens surface of the lens element on the screen side is formed as an aspherical shape, and
10 hence the astigmatism in the marginal area of the image is reduced. Furthermore, with respect to the lens element arranged on the screen side of this lens element, the profile of lens surface on the projection tube side is formed in a convex shape on the
15 projection tube side around the optical axis and a concave shape on the projection tube side in the marginal area and hence the astigmatism in the marginal area of the image can be reduced with higher precision.

20 To realize a reduction in cost which is a problem of the projection lens system having the constitution in the second prior art, the two following means are used.

25 The first means is to form the fluorescent face of a projection tube to be applied to the projection lens

system as a spherical fluorescent face. When the fluorescent face of the projection lens system having a constitution of five group by six elements described in the first embodiment of the second prior art is
5 changed to a spherical surface as it is, the length of optical path from an object point in the marginal area on the fluorescent face to the exit surface of the fifth lens is different between a beam of light passing through the saggital plane and a beam of light
10 passing through the meridional plane, so that a great difference is generated in the focus performance between the saggital direction and the meridional direction because astigmatism conspicuously increases in the marginal area. This trend is specially
15 remarkable in the marginal area between 90% of the distance (relative image height from center to corner) from the center of the screen to each corner and each corner.

Therefore, according to the present invention,
20 when the lens surface of the sixth lens having negative refractive power on the screen side is formed in a profile that the lens action (divergent action) in the lens area through which the light flux from an object in the marginal area on the fluorescent face
25 becomes weaker in comparison with that around the

optical axis of the lens, the difference between the length of optical path on the saggital plane and that on the meridional plane is reduced. Furthermore, when in the lens element arranged on the screen side of the
5 above-mentioned lens element having negative refractive power, the profile of lens surface on the projection tube side is formed in a convex shape on the projection tube side around the optical axis and in a concave shape on the projection tube side in the
10 marginal area, the difference of length of optical path can be made smaller and the astigmatism in the marginal area can be reduced remarkably.

The second means is to change the third lens to inexpensive optical glass.

15 For that purpose, correction of chromatic aberration is realized by a large dispersion plastic concave lens element and an inexpensive small dispersion glass convex lens.

It is also effective to install a filter for
20 cutting the spurious component other than the dominant wavelength component among the light emission spectrum of a phosphorescent substance in at least one lens element of the lenses constituting the projection lens system and reduce the generated chromatic aberration
25 itself.

Furthermore, to realize a large aperture, the
aforementioned large dispersion plastic concave lens
element is formed in a profile of strong aspherical
shape and the aberration is corrected with higher
5 precision. Furthermore, the lens profile is formed in
a concave meniscus profile in which the concave
surface faces the screen side around the optical axis
and particularly in a profile that with respect to the
lens surface on the projection tube side, the
10 inclination of the lens surface in the marginal area
of lens apart from the optical axis is increased. As a
result, the entrance height of light flux into the
third lens (glass) can be decreased and the diameter
of the third lens (glass) can be made smaller when the
15 same F-number is to be obtained, so that the cost can
be reduced.

On the other hand, the projection lens system of
the present invention is structured so that at least
one communicating opening or communicating window
20 extending outside of the projection lens system from
the spaces between the lens elements is installed.

Furthermore, at least one space among the spaces
between the lens elements is structured so that the
communicating opening or communicating window is
25 arranged individually in each of at least two leveling

locations practically on the basis of the horizontal plane in the operation status of the projection lens system or continuously over those locations. In this case, the communicating opening or communicating
5 window in the low location functions as an inlet of air and the communicating opening or communicating window in the high location functions as an outlet of air.

To install the communicating opening or
10 communicating window, one of the methods (1) to (4) shown below is used or these methods are used together.

(1) Around the connection point of a lens element holding member for holding at least one lens element and covering the spaces among the lens elements and a
15 connection member for connecting the lens element holding member to the image generating source, a communicating opening or communicating window is arranged as a space surrounded by at least the lens element holding member and the connection member. In
20 this case, it is possible that the volume of this space is restricted by the size of protrusion provided in the lens element holding member or the size of protrusion provided in the connection member.

(2) A communicating opening or communicating
25 window is arranged in the lens element holding member

itself.

(3) A lens element holding member comprising a first holding member for holding at least one lens element and a second holding member for fitting and holding the first holding member is structured and a communicating opening or communicating window is arranged between the first holding member and the second holding member. In this case, at least one groove provided in a concave shape on the inner side of the second holding member may be functioned as a communicating opening or communicating window.

(4) A communicating opening or communicating window is arranged around the periphery of the lens element.

When a communicating opening or communicating window is arranged by one of the aforementioned methods, it is desirable to set the space between the lens element arranged closest to the image generating source among a plurality of lens elements and the lens element second closest to the image generating source as a corresponding space.

The aforementioned communicating opening or communicating window is arranged so as to replace heated air in the spaces among the lens elements with air outside the projection lens system. In this case,

new problems may arise that a foreign material such as dust enters from the communicating opening or communicating window and adheres to the lens elements, or an external light enters the projection lens system and the image contrast performance of the projection lens system is lowered, or when the projection lens system is used in a projection type image display apparatus, the image contrast performance of the projection type image display apparatus is remarkably lowered due to light leakage from the inside of the projection lens system.

To eliminate the problems, in the aforementioned projection lens system, in the opening portion of the communicating opening or communicating window toward the outside of the projection lens system, a dust-proof member, for example, a flange-shaped member is arranged in the way to protect the air permeability. Or, the communicating opening or communicating window itself is formed in a bent, or curved, or twisted shape.

In the projection lens system of the present invention, the aforementioned communicating opening or communicating window functions as an air inlet through which air at a low temperature (open air) is introduced and an air outlet through which heated air

is ejected in the space among the lens elements in which the communicating opening or communicating window is provided. By doing this, the efficiency of heat radiation from the lens elements is increased by convection of air and the lens elements are suppressed in rising of temperature and hence the expansion and deformation due to rising of temperature are suppressed and as a result, the lens performance, particularly the focus performance are prevented from lowering.

When a projection type cathode ray tube is used as an image generating source, the projection type cathode ray tube becomes a heat generating source. Therefore, when the aforementioned communicating opening or communicating window is provided in the space between the lens element closest to the projection type cathode ray tube and the lens element second closest to it, the effect of the aforementioned action is remarkable. Air has a property that when it is heated, the specific gravity thereof decreases and it flows upward. Therefore, when the height of location of the communicating opening or communicating window which is used as an air outlet is set higher than the height of location of the communicating opening or communicating window which is used as an

air inlet on the basis of a certain horizontal plane,
a practically sufficient effect can be obtained in the
aforementioned action.

On the other hand, when a dust-proof member is
5 arranged in the opening portion of the communicating
opening or communicating window toward the outside of
the projection lens system when the communicating
opening or communicating window itself is formed in a
bent, or curved, or twisted shape, entry of a foreign
10 material or light into the projection lens system and
light leakage from the inside of the projection lens
system can be prevented. As a result, the contrast
performance of the projection lens system itself will
not be lowered and neither will be readuced the image
15 contrast of the projection type image display
apparatus using the projection lens system.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig. 1 is a cross sectional view showing the
essential section of an embodiment of the projection
20 lens system of the present invention;

Fig. 2 is a cross sectional view showing the
arrangement of lens elements and outline of the ray
tracing result in Embodiment 1 of the projection lens
system of the present invention;

25 Fig. 3 is a cross sectional view showing the

arrangement of lens elements and outline of the ray tracing result in Embodiment 7 of the projection lens system of the present invention;

Fig. 4 is a cross sectional view showing the arrangement of lens elements and outline of the ray tracing result in Embodiment 10 of the projection lens system of the present invention;

Fig. 5 is a drawing showing the definition of the axes of coordinates in the equation of the profile of lens surface;

Fig. 6 is an illustration for explaining differences between the aspherical surface and the spherical surface;

Fig. 7 is a characteristic diagram showing second derivative values of the function indicating the aspherical surface profile of the lens surface of the sixth lens 6 on the screen side;

Fig. 8 is a characteristic diagram showing a deviation of the aspherical surface profile of the lens surface of the sixth lens 6 on the screen side from the spherical surface profile;

Fig. 9 is an MTF characteristic diagram showing the focus performance of Embodiment 1 of the projection lens system of the present invention;

Fig. 10 is an MTF characteristic diagram showing

the focus performance of Embodiment 2 of the
projection lens system of the present invention;

Fig. 11 is an MTF characteristic diagram showing
the focus performance of Embodiment 3 of the
5 projection lens system of the present invention;

Fig. 12 is an MTF characteristic diagram showing
the focus performance of Embodiment 4 of the
projection lens system of the present invention;

Fig. 13 is an MTF characteristic diagram showing
10 the focus performance of Embodiment 5 of the
projection lens system of the present invention;

Fig. 14 is an MTF characteristic diagram showing
the focus performance of Embodiment 6 of the
projection lens system of the present invention;

15 Fig. 15 is an MTF characteristic diagram showing
the focus performance of Embodiment 7 of the
projection lens system of the present invention;

Fig. 16 is an MTF characteristic diagram showing
the focus performance of Embodiment 8 of the
20 projection lens system of the present invention;

Fig. 17 is an MTF characteristic diagram showing
the focus performance of Embodiment 9 of the
projection lens system of the present invention;

Fig. 18 is an MTF characteristic diagram showing
25 the focus performance of Embodiment 10 of the

projection lens system of the present invention;

Fig. 19 is a characteristic diagram showing an example of general light emission spectrum characteristics of green phosphorescent substance;

5 Fig. 20 is a cross sectional view showing the essential section of an example of a projection lens system of the prior art;

Fig. 21 is a cross sectional view showing the essential section of the 11th embodiment of the
10 projection lens system of the present invention;

Fig. 22 is a cross sectional view showing the essential section when the cross section of the lens barrel 9 of the projection lens system shown in Fig. 21 is seen in the direction of the arrow A;

15 Fig. 23 is a cross sectional view showing the essential section of the 12th embodiment of the projection lens system of the present invention;

Fig. 24 is a perspective view of the essential section showing the actual constitution of the first
20 communicating opening 27 shown in Fig. 23;

Fig. 25 is a cross sectional view showing the essential section of the 13th embodiment of the projection lens system of the present invention;

25 Fig. 26 is a cross sectional view showing the essential section of the 14th embodiment of the

projection lens system of the present invention;

Fig. 27 is a cross sectional view showing the essential section of the 15th embodiment of the projection lens system of the present invention;

5 Fig. 28 is a cross sectional view showing the essential section of the longitudinal cross section of a rear projection type image display apparatus using the projection lens system of the present invention;

10 Fig. 29 is a cross sectional view showing the essential section of the longitudinal cross section of another embodiment of a rear projection type image display apparatus using the projection lens system of the present invention;

15 Fig. 30 is a cross sectional view showing the projection lens system of the rear projection type image display apparatus shown in Fig. 28 in detail; and

20 Fig. 31 is a cross sectional view showing the projection lens system of the rear projection type image display apparatus shown in Fig. 29 in detail.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The embodiments of the present invention will be explained hereunder with reference to the accompanying drawings.

25 Fig. 1 is a cross sectional view showing the

essential section of an embodiment of the projection lens system of the present invention.

In Fig. 1, numeral 1 indicates a first lens, 2 a second lens, 3 a third lens, 4 a fourth lens, 5 a fifth lens, 6 a sixth lens, 7 a liquid coolant, 8 a projection type cathode ray tube (hereinafter abbreviated to projection tube) which is an image generating source, 8a a face panel of the projection tube, P1 a fluorescent face of the projection tube, and 9 a lens barrel. The lens barrel 9 is separated into an inner barrel 9a and an outer barrel 9b and the inner barrel 9a includes the first lens to the fifth lens which are incorporated and is fixed to the outer barrel 9b with a set screws 12. Furthermore, the outer barrel 9b is fixed to a coupling bracket 11 via a holding plate 13 with screws (not shown in the drawing). The system is structured so as to enlarge and project an image on the fluorescent face of the projection tube P1 which is an object surface on a screen 14.

Tables 1 to 10 (Embodiments 1, 2, 3, ---, and 10 are used respectively) show actual lens data which can be fetched by the projection lens system of the present invention.

Table 1

f=90.49 mm, F_{NO}=0.96

		Radius of curvature RD	Axial distance between surfaces	Abbe's number vd/refractive index
5	Screen	∞	1042.6	1.0
	1st lens	S ₁	8.874	57.9/1.49334
		S ₂	15.473	1.0
	2nd lens	S ₃	9.200	57.9/1.49334
		S ₄	8.7068	1.0
10	3rd lens	S ₅	25.000	61.25/1.59137
		S ₆	1.080	1.0
	4th lens	S ₇	4.000	30.30/1.58890
		S ₈	10.80	1.0
	5th lens	S ₉	8.400	57.9/1.49334
S ₁₀		30.000	1.0	
15	6th lens	S ₁₁	3.405	57.9/1.49334
		S ₁₂	11.49	1.44704
	Transparent medium	∞		
	Cathode-ray tube panel	Face Fluorescent face P ₁	14.10	1.56232

Lens	Surface	CC	AE	AF	AG	AH
1st lens	S ₁	-14.205306	1.27801xE-6	-1.35740xE-9	3.77495xE-13	-3.40452xE-17
	S ₂	1.5000000	-9.32634xE-8	1.54377xE-10	-7.28237xE-14	2.08978xE-17
2nd lens	S ₃	8.0000000	2.38533xE-6	1.25739xE-10	-1.02973xE-13	2.20148xE-17
	S ₄	8.3999996	1.91166xE-6	-5.03454xE-10	1.55701xE-13	-1.27999xE-17
4th lens	S ₇	0.0000	0.0000	0.0000	0.0000	0.0000
	S ₈	0.0000	-1.74446xE-7	1.55853xE-10	-1.07123xE-13	2.70771xE-17
5th lens	S ₉	-15.300000	-2.64597xE-7	1.96982xE-9	-1.17973xE-12	1.13858xE-16
	S ₁₀	0.000	9.74735xE-7	1.85426xE-9	-7.84582xE-13	4.27076xE-17
6th lens	S ₁₁	0.000	-1.34293xE-6	7.37058xE-10	1.53851xE-13	2.42038xE-17

25
$$Z = \frac{r^2 / RD}{1 + \sqrt{1 - (1 + CC)r^2 / RD^2}} + AE \cdot r^4 + AF \cdot r^6 + AG \cdot r^8 + AH \cdot r^{10}$$

Table 2

f=90.31 mm, F_{NO}=1.02

	Screen	Lens surface	Radius of curvature RD	Axial distance between surfaces	Abbe's number vd/refractive index
			∞	1042.6	1.0
5	1st lens	S ₁	85.301	8.874	57.9/1.49334
		S ₂	248.10	20.146	1.0
	2nd lens	S ₃	-596.50	9.200	57.9/1.49334
		S ₄	-590.00	4.9334	1.0
	3rd lens	S ₅	81.066	22.700	61.25/1.59137
		S ₆	-235.00	1.080	1.0
	4th lens	S ₇	-270.00	4.000	30.30/1.58890
		S ₈	-450.00	10.80	1.0
10	5th lens	S ₉	18535.00	8.400	57.9/1.49334
		S ₁₀	-241.19	30.000	1.0
	6th lens	S ₁₁	-56.000	3.405	57.9/1.49334
		S ₁₂	-58.000	11.49	1.44704
	Transparent medium		∞		
15	Cathode-ray tube panel	Face Fluorescent face P ₁	-350.00	14.10	1.56232

Lens	Surface	CC	AE	AF	AG	AH
1st lens	S ₁	-14.205306	1.92669xE-6	-1.85054xE-9	5.75077xE-13	-6.05405xE-17
	S ₂	1.5000000	7.18758xE-8	-4.05008xE-10	2.13188xE-13	-1.61270xE-17
2nd lens	S ₃	8.0000000	2.07465xE-6	4.74347xE-11	6.19323xE-14	-1.81834xE-17
	S ₄	8.3999996	1.76511xE-6	-2.71126xE-10	1.43099xE-13	-2.74519xE-17
4th lens	S ₇	0.0000	0.0000	0.0000	0.0000	0.0000
	S ₈	0.0000	-3.76560xE-7	1.20340xE-10	-3.00848xE-14	6.05881xE-18
5th lens	S ₉	-15.300000	-2.64597xE-7	1.96982xE-9	-1.17973xE-12	1.13858xE-16
	S ₁₀	0.000	1.16291xE-6	1.80247xE-9	-7.02182xE-13	1.93070xE-17
6th lens	S ₁₁	0.000	-1.59847xE-6	1.35363xE-9	-6.40009xE-13	1.66139xE-16

25
$$Z = \frac{r^2 / RD}{1 + \sqrt{1 - (1 + CC)r^2 / RD^2}} + AE \cdot r^4 + AF \cdot r^6 + AG \cdot r^8 + AH \cdot r^{10}$$

Table 3

f=90.77 mm, F_{No}=1.01

		Radius of curvature RD	Axial distance between surfaces	Abbe's number vd/refractive index	
5	Screen	∞	1042.6	1.0	
	1st lens	S ₁	106.180	8.874	57.9/1.49334
		S ₂	267.06	18.075	1.0
	2nd lens	S ₃	-1483.80	9.200	57.9/1.49334
		S ₄	-339.15	9.1674	1.0
	3rd lens	S ₅	76.594	22.700	61.25/1.59137
		S ₆	-235.00	1.080	1.0
	4th lens	S ₇	-270.00	4.000	30.30/1.58890
		S ₈	-450.00	10.80	1.0
	5th lens	S ₉	18535.00	8.400	57.9/1.49334
S ₁₀		-577.72	30.000	1.0	
6th lens	S ₁₁	-55.500	3.405	57.9/1.49334	
	S ₁₂	-58.000	11.49	1.44704	
Transparent medium		∞			
15	Cathode-ray tube panel	Face Fluorescent face P ₁	14.10	1.56232	
			-350.00		

Lens	Surface	CC	AE	AF	AG	AH
1st lens	S ₁	-14.205306	-4.17615xE-7	-7.58755xE-10	3.11083xE-13	-3.26331xE-17
	S ₂	1.5000000	-1.25741xE-6	5.87530xE-10	-1.83314xE-13	3.84552xE-17
2nd lens	S ₃	8.0000000	2.05903xE-6	7.77375xE-10	-3.99801xE-13	7.17568xE-17
	S ₄	8.3999996	1.58107xE-6	3.39912xE-10	-1.74104xE-13	3.07068xE-17
4th lens	S ₇	0.0000	0.0000	0.0000	0.0000	0.0000
	S ₈	0.0000	-5.47788xE-7	3.08341xE-10	-6.34311xE-14	9.31559xE-18
5th lens	S ₉	-15.300000	-3.22064xE-7	2.42981xE-9	-1.69278xE-12	2.46305xE-16
	S ₁₀	0.000	1.58758xE-6	2.05251xE-9	-9.15005xE-13	5.00000xE-17
6th lens	S ₁₁	0.000	-1.62384xE-6	1.46180xE-9	-6.25537xE-13	1.79061xE-16

25
$$Z = \frac{r^2 / RD}{1 + \sqrt{1 - (1 + CC)r^2 / RD^2}} + AE \cdot r^4 + AF \cdot r^6 + AG \cdot r^8 + AH \cdot r^{10}$$

Table 4

f=89.47 mm, F_{no}=1.00

		Radius of curvature RD	Axial distance between surfaces	Abbe's number vd/refractive index	
5	Screen	∞	1042.6	1.0	
	1st lens	S ₁	87.060	8.874	57.9/1.49334
		S ₂	166.59	13.907	1.0
	2nd lens	S ₃	-737.56	9.200	57.9/1.49334
		S ₄	-188.83	10.482	1.0
	3rd lens	S ₅	90.712	22.700	61.25/1.59137
		S ₆	-235.00	1.080	1.0
	4th lens	S ₇	-270.00	4.000	30.30/1.58890
		S ₈	-450.00	10.80	1.0
	10	5th lens	S ₉	18535.00	8.400
S ₁₀			-241.19	30.000	1.0
6th lens		S ₁₁	-52.268	3.405	57.9/1.49334
		S ₁₂	-58.000	11.49	1.44704
15	Transparent medium	∞			
	Cathode-ray tube panel	Face Fluorescent face P ₁	-350.00	14.10	1.56232

Lens	Surface	CC	AE	AF	AG	AH
1st lens	S ₁	-14.205306	1.81161xE-6	-1.81880xE-9	4.93904xE-13	-4.44977xE-17
	S ₂	1.5000000	4.78526xE-7	-5.76838xE-10	3.61505xE-13	-5.85045xE-17
2nd lens	S ₃	8.0000000	1.05968xE-6	2.18392xE-10	3.29367xE-15	-9.38718xE-18
	S ₄	8.3999996	6.04039xE-7	-1.05414xE-10	2.82509xE-14	1.17689xE-17
4th lens	S ₇	0.0000	0.0000	0.0000	0.0000	0.0000
	S ₈	0.0000	-5.23821xE-7	3.86150xE-11	3.41462xE-16	1.15405xE-18
5th lens	S ₉	-15.300000	-2.81921xE-7	1.77440xE-9	-1.02161xE-12	1.07908xE-16
	S ₁₀	0.000	1.16291xE-6	1.80247xE-9	-7.02182xE-13	1.93070xE-17
6th lens	S ₁₁	0.000	-8.30584xE-7	-3.19962xE-10	7.06789xE-13	-2.63143xE-16

25
$$Z = \frac{r^2 / RD}{1 + \sqrt{1 - (1 + CC)r^2 / RD^2}} + AE \cdot r^4 + AF \cdot r^6 + AG \cdot r^8 + AH \cdot r^{10}$$

Table 5

f=90.13 mm, F_{no}=1.00

		Radius of curvature RD	Axial distance between surfaces	Abbe's number vd/refractive index	
5	Screen	∞	1042.6	1.0	
	1st lens	S ₁	112.98	8.874	57.9/1.49334
		S ₂	415.40	17.286	1.0
	2nd lens	S ₃	-562.36	9.200	57.9/1.49334
		S ₄	-339.15	8.1494	1.0
	3rd lens	S ₅	76.594	22.700	61.25/1.59137
		S ₆	-235.00	3.080	1.0
	4th lens	S ₇	-270.00	4.000	30.30/1.58840
		S ₈	-450.00	9.300	1.0
	5th lens	S ₉	18535.00	8.400	57.9/1.49334
		S ₁₀	-400.00	29.500	1.0
	6th lens	S ₁₁	-55.499	3.405	57.9/1.49334
S ₁₂		-58.000	11.49	1.44704	
10	Transparent medium	∞			
	Cathode-ray tube panel	Face Fluorescent face P ₁	-350.00	14.1	1.56232
15					

Lens	Surface	CC	AE	AF	AG	AH
1st lens	S ₁	-14.205306	-4.99132xE-7	-7.52281xE-10	3.04572xE-13	-3.17985xE-17
	S ₂	1.500000	-9.63142xE-7	-4.48452xE-10	-1.48606xE-13	3.24547xE-17
2nd lens	S ₃	8.000000	2.70666xE-6	3.50490xE-10	-2.62215xE-13	4.22459xE-17
	S ₄	8.340000	2.08869xE-6	-1.90134xE-10	2.77475xE-14	-1.42593xE-17
4th lens	S ₇	0.000000	-7.29331xE-7	-1.99626xE-10	6.48129xE-15	-1.12055xE-18
	S ₈	0.000000	-1.29715xE-6	1.84357xE-10	-1.46193xE-13	2.60704xE-17
5th lens	S ₉	-15.300000	-1.70710xE-7	2.13023xE-9	-1.37605xE-12	1.09708xE-16
	S ₁₀	0.000000	1.58758xE-6	2.05252xE-9	-9.15005xE-13	5.00000xE-17
6th lens	S ₁₁	0.000000	-1.89756xE-6	1.72825xE-9	-1.08034xE-12	3.39635xE-16

25
$$Z = \frac{r^2 / RD}{1 + \sqrt{1 - (1 + CC)r^2 / RD^2}} + AE \cdot r^4 + AF \cdot r^6 + AG \cdot r^8 + AH \cdot r^{10}$$

Table 6

f=90.28 mm, F_{NO}=1.00

	Screen	Lens surface	Radius of curvature RD	Axial distance between surfaces	Abbe's number vd/refractive index
			∞	1050.0	1.0
5	1st lens	S ₁	115.670	8.874	57.9/1.49334
		S ₂	335.03	17.162	1.0
	2nd lens	S ₃	-1054.40	9.200	57.9/1.49334
		S ₄	-261.89	5.8105	1.0
	3rd lens	S ₅	71.717	22.700	61.25/1.59137
		S ₆	-325.88	2.267	1.0
	4th lens	S ₇	-290.07	4.000	30.30/1.58890
		S ₈	5000.00	9.300	1.0
10	5th lens	S ₉	928.70	8.400	57.9/1.49334
		S ₁₀	-336.67	30.189	1.0
	6th lens	S ₁₁	-54.636	3.405	57.9/1.49334
		S ₁₂	-58.000	11.49	1.44704
	Transparent medium		∞		
15	Cathode-ray tube panel	Face Fluorescent face P ₁	-350.00	14.10	1.56232

Lens	Surface	CC	AE	AF	AG	AH
1st lens	S ₁	-14.898250	-7.47696xE-7	-7.73792xE-10	3.44880xE-13	-3.75545xE-17
	S ₂	5.5688664	-1.09894xE-6	5.28791xE-10	-2.05281xE-13	4.66837xE-17
2nd lens	S ₃	-2316.3117	2.54450xE-6	5.62992xE-10	-3.61632xE-13	5.44320xE-17
	S ₄	11.690594	1.79735xE-6	4.46261xE-11	-1.10792xE-13	6.60349xE-18
20	4th lens	S ₇	22.120667	-5.45630xE-7	-1.25450xE-10	1.70354xE-14
	S ₈	-719.55890	-1.28076xE-6	1.68255xE-10	-1.91393xE-13	3.00716xE-17
	5th lens	S ₉	-15.300000	-4.49218xE-7	1.60071xE-9	-1.19463xE-12
	S ₁₀	0.00000	1.58758xE-6	2.05251xE-9	-9.15005xE-13	5.00000xE-17
	6th lens	S ₁₁	-0.5923559	-1.91950xE-6	1.26443xE-9	-7.45525xE-13
						2.90386xE-16

25
$$Z = \frac{r^2 / RD}{1 + \sqrt{1 - (1 + CC)r^2 / RD^2}} + AE \cdot r^4 + AF \cdot r^6 + AG \cdot r^8 + AH \cdot r^{10}$$

Table 7

f=90.34 mm, F_{no}=1.00

		Radius of curvature RD	Axial distance between surfaces	Abbe's number vd/refractive index	
5	Screen	∞	1050.0	1.0	
	1st lens	S ₁	114.560	8.874	57.9/1.49334
		S ₂	299.87	17.162	1.0
	2nd lens	S ₃	-866.97	9.200	57.9/1.49334
		S ₄	-239.70	5.0793	1.0
	3rd lens	S ₅	71.114	22.700	61.25/1.59137
		S ₆	-378.83	2.737	1.0
	4th lens	S ₇	-287.97	4.000	30.30/1.58890
		S ₈	4000.00	9.300	1.0
	10	5th lens	S ₉	613.06	8.400
S ₁₀			-344.07	30.312	1.0
6th lens		S ₁₁	-54.393	3.405	57.9/1.49334
	S ₁₂	-58.000	11.490	1.44704	
15	Transparent medium	∞			
	Cathode-ray tube panel	Face Fluorescent face P ₁	-350.00	14.10	1.56232

Lens	Surface	CC	AE	AF	AG	AH
1st lens	S ₁	-13.429961	-8.40169xE-7	-7.76450xE-10	3.51328xE-13	-3.82801xE-17
	S ₂	-3.3351539	-1.11543xE-6	5.31625xE-10	-2.10620xE-13	4.81196xE-17
2nd lens	S ₃	-959.82674	2.58831xE-6	5.51215xE-10	-3.56294xE-13	5.36534xE-17
	S ₄	10.354769	1.80263xE-6	7.19625xE-11	-1.18864xE-13	7.75962xE-18
4th lens	S ₇	22.120667	-5.45610xE-7	-1.25450xE-10	1.70354xE-14	-1.41437xE-17
	S ₈	-3630.1763	-1.25638xE-6	1.51585xE-10	-1.90122xE-13	3.04799xE-17
5th lens	S ₉	-15.300000	-4.18973xE-7	1.51153xE-9	-1.11826xE-12	1.08743xE-16
	S ₁₀	0.000	1.58758xE-6	2.05251xE-9	-9.15005xE-13	4.99999xE-17
6th lens	S ₁₁	-0.354248	-1.33128xE-6	1.27556xE-9	-6.55222xE-13	3.04020xE-16

25
$$Z = \frac{r^2 / RD}{1 + \sqrt{1 - (1 + CC)r^2 / RD^2}} + AE \cdot r^4 + AF \cdot r^6 + AG \cdot r^8 + AH \cdot r^{10}$$

Table 8

f=90.10 mm, F_{NO}=1.00

		Radius of curvature RD	Axial distance between surfaces	Abbe's number vd/refractive index	
5	Screen	∞	1042.6	1.0	
	1st lens	S ₁	110.91	8.874	57.9/1.49334
		S ₂	393.88	17.431	1.0
	2nd lens	S ₃	-562.36	9.200	57.9/1.49334
		S ₄	-339.15	7.8423	1.0
	3rd lens	S ₅	76.594	22.700	61.25/1.59137
		S ₆	-235.00	2.080	1.0
	4th lens	S ₇	-270.00	4.000	30.30/1.58840
		S ₈	-450.00	10.300	1.0
	5th lens	S ₉	18535.00	8.400	57.9/1.49334
		S ₁₀	-400.00	29.500	1.0
	6th lens	S ₁₁	-55.499	3.405	57.9/1.49334
S ₁₂		-58.000	11.49	1.44704	
Transparent medium		∞			
15	Cathode-ray tube panel	Face Fluorescent face P ₁	14.1	1.56232	
		-350.00			

Lens	Surface	CC	AE	AF	AG	AH
1st lens	S ₁	-14.205306	-3.49264xE-7	-7.51764xE-10	2.98572xE-13	-3.16781xE-17
	S ₂	1.500000	-8.62273xE-7	4.44555xE-10	-1.36020xE-13	2.95057xE-17
2nd lens	S ₃	8.000000	2.63183xE-6	3.36531xE-10	-2.58187xE-13	4.36505xE-17
	S ₄	8.340000	2.02573xE-6	-2.24606xE-10	2.83556xE-14	-1.05000xE-17
4th lens	S ₇	0.000000	-5.45630xE-7	-1.25450xE-10	1.70354xE-14	-1.41437xE-17
	S ₈	0.000000	-1.02404xE-6	2.45508xE-10	-1.44920xE-13	1.38124xE-17
5th lens	S ₉	-15.300000	-7.06392xE-7	2.06151xE-9	-1.30794xE-12	7.28924xE-17
	S ₁₀	0.000000	1.58758xE-6	2.05252xE-9	-9.15005xE-13	5.00000xE-17
6th lens	S ₁₁	0.000000	-1.82729xE-6	1.68806xE-9	-1.07491xE-12	3.50966xE-16

25
$$Z = \frac{r^2 / RD}{1 + \sqrt{1 - (1 + CC)r^2 / RD^2}} + AE \cdot r^4 + AF \cdot r^6 + AG \cdot r^8 + AH \cdot r^{10}$$

Table 9

f=90.33 mm, F_{NO}=1.00

		Radius of curvature RD	Axial distance between surfaces	Abbe's number vd/refractive index
	Screen	∞	1050.0	1.0
5	1st lens	S ₁ 109.780	8.874	57.9/1.49334
		S ₂ 386.22	16.778	1.0
	2nd lens	S ₃ -562.36	9.200	57.9/1.49334
		S ₄ -339.15	10.013	1.0
	3rd lens	S ₅ 76.594	22.300	61.25/1.59137
		S ₆ -235.00	2.080	1.0
	4th lens	S ₇ -270.00	4.000	30.30/1.58890
		S ₈ -450.00	10.300	1.0
10	5th lens	S ₉ 18535.00	8.400	57.9/1.49334
		S ₁₀ -400.00	29.500	1.0
	6th lens	S ₁₁ -55.499	3.405	57.9/1.49334
		S ₁₂ -58.000	11.49	1.44704
	Transparent medium	∞		
15	Cathode-ray tube panel	Face Fluorescent face P ₁ -350.00	14.10	1.56232

Lens	Surface	CC	AE	AF	AG	AH
1st lens	S ₁	-14.205306	-3.77711xE-7	-6.80543xE-10	2.76889xE-13	-2.92638xE-17
	S ₂	1.5000000	-9.39630xE-7	5.48052xE-10	-1.69877xE-13	3.37537xE-17
2nd lens	S ₃	8.0000000	2.50070xE-6	4.30750xE-10	-2.98735xE-13	5.40955xE-17
	S ₄	8.4000000	1.94248xE-6	-1.45666xE-10	-7.76624xE-15	3.96630xE-18
20	4th lens	S ₇	0.000000	-1.11617xE-7	-2.69651xE-11	-1.97791xE-15
	S ₈	0.000000	-5.02307xE-7	3.06274xE-10	-1.28546xE-13	-1.80677xE-19
	5th lens	S ₉	-15.300000	2.76587xE-8	2.13667xE-9	-1.35824xE-12
	S ₁₀	0.00000	1.58758xE-6	2.05251xE-9	-9.15005xE-13	5.00000xE-17
	6th lens	S ₁₁	0.00000	-1.62935xE-6	1.40012xE-9	-7.34993xE-13
						2.07431xE-16

25
$$Z = \frac{r^2 / RD}{1 + \sqrt{1 - (1 + CC)r^2 / RD^2}} + AE \cdot r^4 + AF \cdot r^6 + AG \cdot r^8 + AH \cdot r^{10}$$

Table 10

f=90.28 mm, F_{ND}=1.00

			Radius of curvature RD	Axial distance between surfaces	Abbe's number vd/refractive index
5	Screen	Lens surface	∞	1042.6	1.0
	1st lens	S ₁	110.220	8.874	57.9/1.49334
		S ₂	376.07	16.478	1.0
	2nd lens	S ₃	-562.36	9.200	57.9/1.49334
		S ₄	-339.15	8.9875	1.0
10	3rd lens	S ₅	76.594	22.700	61.25/1.59137
		S ₆	-235.00	3.080	1.0
	4th lens	S ₇	-270.00	4.000	30.30/1.58890
		S ₈	-450.00	9.300	1.0
	5th lens	S ₉	18535.00	8.400	57.9/1.49334
		S ₁₀	-400.00	29.500	1.0
	6th lens	S ₁₁	-55.499	3.405	57.9/1.49334
		S ₁₂	-58.000	11.490	1.44704
	Transparent medium		∞		
	Cathode-ray tube panel	Face Fluorescent face P ₁	-350.00	14.10	1.56232

Lens	Surface	CC	AE	AF	AG	AH
1st lens	S ₁	-14.205306	-6.05201xE-7	-7.33372xE-10	3.22224xE-13	-3.52762xE-17
	S ₂	1.5000000	-1.21465xE-6	6.09643xE-10	-1.89740xE-13	3.97475xE-17
2nd lens	S ₃	8.0000000	2.38762xE-6	6.05052xE-10	-3.78418xE-13	5.98085xE-17
	S ₄	8.4000000	1.78170xE-6	6.59630xE-11	-1.20208xE-13	1.50850xE-17
4th lens	S ₇	0.000000	-5.45630xE-7	-1.25450xE-10	1.70354xE-14	-1.41437xE-17
	S ₈	0.000000	-1.10393xE-6	3.73070xE-10	-2.13647xE-13	2.70690xE-17
5th lens	S ₉	-15.300000	-3.51269xE-8	2.02646xE-9	-1.25938xE-12	8.23050xE-17
	S ₁₀	0.00000	1.58758xE-6	2.05251xE-9	-9.15005xE-13	4.99999xE-17
6th lens	S ₁₁	0.00000	-1.90908xE-6	1.65847xE-9	-9.59000xE-13	2.77588xE-16

25
$$Z = \frac{r^2 / RD}{1 + \sqrt{1 - (1 + CC)r^2 / RD^2}} + AE \cdot r^4 + AF \cdot r^6 + AG \cdot r^8 + AH \cdot r^{10}$$

According to the embodiments of the present invention, the focal length of the single sixth lens and the focal length of the overall projection lens system synthesizing every lens are calculated
5 including the face panel 8a of the projection tube, the liquid coolant 7, and the fluorescent face P1.

Figs. 2, 3, and 4 are cross sectional views showing the arrangement of lens elements and outline of the ray tracing result in the projection lens
10 system shown in Embodiments 1, 7, and 10 and the lens barrel and other components are omitted from reason of explanation. The lens profile and arrangement shown in Fig. 4 are the same as those shown in Fig. 1.

The projection lens system used in the embodiments
15 of the present invention is structured so that when rasters with a diagonal of 5.33 inch are displayed on the fluorescent face of the projection tube P1 and enlarged and projected as image with a diagonal of 60 inch onto the screen, a best performance can be
20 obtained. The semi-field angle of the projection lens system is 360 and a wide field angle is realized. Therefore, as described later, in a rear projection type image display apparatus such as a projection television set having a constitution of one reflecting
25 mirror for folding the light path, a sufficiently

compact set can be realized.

Next, how to read the lens data will be explained on the basis of Table 1. Table 1 divides and displays data into spherical surface data mainly handling the lens area in the neighborhood of the optical axis and aspherical surface data in the marginal area thereof.

The table shows that the radius of curvature of the screen is infinity (that is, a plane), and the distance (axial distance between surfaces) on the optical axis from the screen to the surface S1 of the first lens 1 is 1042.6 mm, and the refractive index of the medium between them is 1.0. The table also shows that the radius of curvature of the lens surface S1 is 91.403 mm (the center of curvature is on the image generating source side), and the distance (axial distance between surfaces) on the optical axis between the lens surfaces S1 and S2 is 8.874 mm, and the refractive index of the medium between them is 1.49334. In the same way, the table shows lastly that the radius of curvature of the fluorescent face P1 of the face panel 8a of the projection tube is 350 mm, and the thickness of the face panel of the projection tube on the optical axis is 14.10 mm, and the refractive index thereof is 1.56232. The transparent medium described in each table indicates the aforementioned

liquid coolant 7.

With respect to the surfaces S1 and S2 of the first lens 1, the surfaces S3 and S4 of the second lens 2, the surfaces S7 and S8 of the fourth lens 4, the surfaces S9 and S10 of the fifth lens 5, and the surface S11 of the sixth lens 6, aspherical coefficients are shown.

The aspherical coefficients are constants when the profile of lens surface is expressed by the following equation. The exponent expression in each table uses a base of 10.

$$Z(r) = \frac{r^2 / RD}{1 + \sqrt{1 - (1 + CC)r^2 / RD^2}} \quad (\text{Equation 1})$$
$$+ AE \cdot r^4 + AF \cdot r^6 + AG \cdot r^8 + AH \cdot r^{10} + \dots + A \cdot r^{2n}$$

where RD, CC, AE, AF, AG, AH, ---, and A indicate arbitrary constants and n indicates an arbitrary natural number. S5 and S6 indicate surfaces of the third lens 3. S13 indicates a surface of the face panel of the projection tube and S12 indicates another surface of the sixth lens 6.

Fig. 5 is a drawing showing the definition of the axes of coordinates in Equation 1 of the aforementioned profile of lens surface, and the direction of optical axis from the screen toward the image generating source is set as a Z axis, and the

radial direction of lens is set as an r axis. In this case, $Z(r)$ indicates the height of lens surface (surface sag). r indicates the distance from the optical axis of the system, and RD indicates the
5 radius of curvature, and CC indicates a conic constant. Therefore, when each coefficient such as CC , AE , AF , AG , and AH is given, the height of lens surface (hereinafter referred to as the surface sag), that is, the profile is decided according to the aforementioned
10 equation.

Fig. 6 is an illustration for explaining differences between the aspherical surface and the spherical surface. In Fig. 6, $As(r)$ indicates a value which is obtained by substituting the values of
15 respective coefficients in Equation 1 of the profile of lens surface $Z(r)$ and $Ss(r)$ indicates a value when only the radius of curvature RD is substituted in Equation 1 of the profile of lens surface $Z(r)$ and the other coefficients are set to 0. As the absolute value
20 of the ratio $((As(r)-Ss(r))/Ss(r))$ of the difference of these values $(As(r)-Ss(r))$ to $Ss(r)$ increases, the degree of the aspherical surface increases in strength.

The above is how to read the data shown in Table 1. With respect to Tables 2 to 10, how to read is the
25 same.

Next, the action of each lens group of the projection lens system of the present invention will be explained hereunder.

5 The first lens 1 has a concave profile in the marginal area as shown in Figs. 2, 3, and 4 and corrects the spherical aberration for the light flux (upper ray RAY1, lower ray RAY2) from an object A on the axis and the coma aberration for the light flux (upper ray RAY3, lower ray RAY4) from an object B in
10 the marginal area. The location (the marginal area of the lens apart from the optical axis of the lens surface on the screen side) through which the light from the upper ray RAY3 to the lower ray RAY4 passes has a profile of aspherical surface which is concave
15 on the screen side.

The second lens 2 has a profile of aspherical surface so that the marginal area of the lens apart from the optical axis of the lens surface on the screen side is convex on the screen side as shown in
20 Figs. 2, 3, and 4 so as to correct astigmatism and coma aberration. When this lens is combined with the first lens 1, the system is structured so that the negative refractive power on the basis of the lens profile (concave) in the marginal area of the first
25 lens and the positive refractive power on the basis of

the lens profile (convex) in the marginal area of the second lens offset each other. Therefore, even if both lens are plastic products, the lowering of the focus performance of the projection lens system due to changes in temperature and absorption of moisture can be suppressed as much as possible.

The third lens 3 is made of glass so as to reduce the drift of the focus performance due to temperature changes and structured so as to increase the positive refractive power as much as possible. According to this embodiment, to reduce the production cost of the projection lens system, SK5 which is inexpensive optical glass is used.

The fourth lens 4 has a meniscus profile which is concave on the screen side as shown in Figs. 2, 3, and 4 or a lens profile which is concave on both sides (the embodiments shown in Tables 6 and 7) in the center area thereof and has an aspherical surface profile which is a meniscus profile which is concave on the screen side in the marginal area thereof.

For the light flux (upper ray RAY1, lower ray RAY2) from the object point A on the axis, the fourth lens 4 corrects the spherical aberration by the concave profile in the marginal area of lens and reduces the chromatic aberration in combination with

the third lens 3 by using a high dispersion material having an Abbe's number of 45 or less.

On the other hand, the fourth lens 4 of the present invention is a lens element with an almost uniform thickness as a whole due to the aforementioned aspherical surface profile and for example, even if a plastic material having poor fluidity for molding such as PC (polycarbonate) is used, a high profile accuracy can be obtained. Furthermore, the lens profile of the fourth lens 4 is a lens profile that the neighborhood of the optical axis has a concave meniscus profile whose concave surface faces the screen side and that particularly with respect to the lens surface on the projection tube side, the inclination of the lens surface in the marginal area of lens apart from the optical axis is large and the lens surface is almost parallel with the lens surface on the screen side. As a result, as shown in Figs. 2 to 4, the upper ray (RAY1, RAY2) of the light flux generated from the object point A on the optical axis can be shifted toward the optical axis. Therefore, the light entry height into the third lens (glass) is lowered and the diameter of a glass lens can be smaller than that is when the same F-number is obtained without the fourth lens. As a result, the cost of a glass lens can be

reduced.

Furthermore, since the inclination of the lens surface in the marginal area of the fourth lens 4 is large, the incident angle into the third lens 3 is increased and the refractive power of the third lens 3 is decreased. Therefore, an inexpensive glass material with a refractive index n_d of 1.6 or less can be used for the third lens and the cost can be reduced.

The fifth lens 5 corrects coma aberration of higher order generated by the light flux (upper ray RAY3, lower ray RAY4) from the object point B in the marginal area as shown in Figs. 2, 3, and 4, so that the profile in the neighborhood of the location (the marginal area of the lens surface on the projection tube side which is an image generating source) through which the lower ray RAY4 passes is an aspherical surface profile which is concave on the projection tube side. The profile in the neighborhood of the location through which the upper ray RAY3 passes is also an aspherical surface profile which is concave locally on the screen side.

Therefore, the lens surface of this lens on the projection tube side has an aspherical surface profile in which the neighborhood of the optical axis is convex on the projection tube side and the marginal

area is concave on the projection tube side as a whole.
To suppress the lowering of the focus performance of
the projection lens system due to changes in
temperature and absorption of moisture as much as
5 possible, the refractive power is made as small as
possible.

The sixth lens 6 corrects the curvature of field
accompanied by the fluorescent face P1. The
fluorescent face P1 is a spherical fluorescent face
10 unlike the prior art 2, so that as shown in Figs. 2, 3,
and 4, the aspherical surface profile of the lens
surface of the sixth lens 6 on the screen side is a
profile that the refractive power in the area through
which the light flux (upper ray RAY3, lower ray RAY4)
15 from the object point B in the marginal area passes is
weaker than the refractive power in the neighborhood
of the optical axis and the sixth lens 6 corrects the
astigmatism at the same time.

Fig. 7 is a characteristic diagram in which values
20 obtained by substituting a distance of r from the
optical axis in a second derivative obtained by
differentiating the function indicating the profile of
aspherical surface of the lens surface of the sixth
lens 6 on the screen side quadratically are graphed.
25 On the lens surfaces by the first prior art (prior art

1) and the second prior art (prior art 2) mentioned above, the absolute values of derivative values between the optical axis and the marginal area of the lens increase monotonously. This shows that the refracting action of the lens increases monotonously from the optical axis toward the marginal area of the lens. On the other hand, in the embodiments of the present invention, a value obtained in the same way has a point of inflection as shown in Embodiment 8 or reduces in an area more than 70% of the effective radius as shown in Embodiments 9 and 10. As a result, it is found that the refracting action of the lens increases once from the optical axis toward the marginal area and decreases thereafter.

Fig. 8 is a characteristic diagram in which the distance of the aspherical surface profile of the lens surface of the sixth lens 6 on the screen side from the lens surface $S_s(r)$ only of the spherical surface system is obtained by calculation. The horizontal axis shown in Fig. 8 indicates a relative value of the aforementioned distance r to the effective lens radius and the vertical axis indicates a difference between $A_s(r)$ and $S_s(r)$. In comparison with the first prior art (prior art 1 shown in the drawing), in the embodiments of the present invention, the difference

between $As(r)$ and $Ss(r)$ is small such as about $1/2$ of that in prior art 1 or less and the marginal area of the sixth lens 6 is not thick but almost uniform in thickness, so that satisfactory moldability can be
5 obtained.

Figs. 9 to 18 are characteristic diagrams showing evaluation results of the focus performance by the MTF (modulation transfer function) when rasters with a diagonal of 5.33 inch are displayed on the fluorescent
10 face of the projection tube using the aforementioned projection lens system of the present invention and enlarged and displayed on the screen (60 inch) and correspond to Embodiments 1, 2, 3, ---, and 10 sequentially. The horizontal axis in these drawings
15 indicates a relative image height from center on the screen.

As a spatial frequency as an evaluation condition, a case that 300 TV lines are taken as a stripe signal of white and black on the screen, that is, 150 pair
20 lines are taken for the longitudinal dimension of the screen is shown. As shown in these drawings, by the projection lens system having this constitution, a satisfactory MTF characteristic can be obtained.

On the other hand, when three primary-color
25 projection tube of red, green, and blue are used as

projection tubes which is image generating sources,
the spurious component other than the dominant wave
length component is generally included in the light
emission spectrum of the phosphorescent substance of
5 each projection tube.

Fig. 19 is a characteristic diagram showing an
example of the light emission spectrum of a general
green phosphorescent substance. In the green light
emission spectrum shown in Fig. 19, a spurious
10 component of several wave lengths can be seen in
addition to a dominant wave length component of 545 nm.

If a filter for cutting the aforementioned
spurious component is installed in at least one of the
lens elements constituting the projection lens system
15 so as to reduce the generated chromatic aberration
itself, a more satisfactory focus performance can be
obtained.

Next, power distribution to each lens group in the
aforementioned embodiments of the projection lens
20 system of the present invention will be explained.

Table 11 is a table showing power distribution
when the focal length of the overall projection lens
system is assumed as f_0 and the focal lengths of the
first lens 1, second lens 2, third lens 3, fourth lens
25 4, fifth lens 5, and sixth lens 6 are assumed as f_1 ,

f_2 , f_3 , f_4 , f_5 , and f_6 respectively in the embodiments of the present invention shown in Tables 1 to 10.

The ranges of power distribution shown in Table 11 are shown below.

5 $0.24 < f_0/f_1 < 0.35$

$0.0 < f_0/f_2 < 0.18$

$0.78 < f_0/f_3 < 0.91$

$-0.20 < f_0/f_4 < 0.0$

$0.0 < f_0/f_5 < 0.21$

10 $-0.61 < f_0/f_6 < -0.55$

According to this embodiment, by sharing the greater part of the positive refractive power of the overall projection lens system by the third lens which is a glass lens element, the drift of the focus
15 performance by temperature change is reduced.

Table 11

Lens No.	Lens power distribution						Focal length f_0
	f_0/f_1	f_0/f_1	f_0/f_3	f_0/f_4	f_0/f_5	f_0/f_6	(mm)
1	0.3343	0.00121	0.8617	-0.0783	0.2008	-0.5550	90.486
2	0.3489	0.00121	0.8624	-0.0781	0.1871	-0.5544	90.310
3	0.2587	0.1021	0.9041	-0.0785	0.0799	-0.5640	90.775
4	0.2510	0.1749	0.7875	-0.0774	0.1854	-0.6037	89.473
5	0.2893	0.0527	0.8977	-0.0780	0.1135	-0.5602	90.130
6	0.2555	0.1283	0.8889	-0.1940	0.1798	-0.5734	90.276
7	0.2442	0.1352	0.8755	-0.1981	0.2016	-0.5773	90.339
8	0.2909	0.0527	0.8974	-0.0780	0.1135	-0.5600	90.098
9	0.2936	0.0529	0.9001	-0.0782	0.1138	-0.5614	90.330
10	0.2888	0.0528	0.8992	-0.0781	0.1138	-0.5611	90.277

f_0 : Focal length of overall lens system (mm)
 f_1 : Focal length of first lens (mm)
 f_2 : Focal length of second lens (mm)
 f_3 : Focal length of third lens (mm)
 f_4 : Focal length of fourth lens (mm)
 f_5 : Focal length of fifth lens (mm)
 f_6 : Focal length of sixth lens (mm)

Next, characteristics of the profile of lens surface will be explained.

The profiles of aspherical surfaces of the lens surface S1 of the first lens 1 on the screen side, the lens surface S8 of the fourth lens 4 on the image generating source side, the lens surface S10 of the fifth lens 5 on the image generating source side, and the lens surface S11 of the sixth lens 6 on the screen side have the following characteristics.

In Fig. 6, $As(r)$ indicates a value which is obtained by substituting the values of respective

coefficients in Equation 1 of the profile of lens surface $Z(r)$ and $Ss(r)$ indicates a value when only the radius of curvature RD is substituted in Equation 1 of the profile of lens surface $Z(r)$ and the other
5 coefficients are set to 0. In this case, the value of $As(r)/Ss(r)$ is assumed as an index indicating the degree of the aspherical surface. In this case, the aforementioned ratio of As and Ss of the lens surface $S1$ of the first lens 1 on the screen side is within
10 the following range as shown in Table 12.

$$(As/Ss) > -0.1$$

The aforementioned ratio of As and Ss of the lens surface $S8$ of the fourth lens 4 on the image generating source side is within the following range
15 as shown in Table 13.

$$(As/Ss) > -21.2$$

Furthermore, the aforementioned ratio of As and Ss of the lens surface $S10$ of the fifth lens 5 on the image generating source side is within the following
20 range as shown in Table 14.

$$(As/Ss) < -0.6$$

Furthermore, the aforementioned ratio of As and Ss of the lens surface $S11$ of the sixth lens 6 on the screen side is within the following range as shown in Table
25 15.

$$(A_s/S_s) < 1.1$$

Next, the condition for making the light amount ratio of the middle field of the screen satisfactory and some other conditions will be described. Assuming the distance (axial distance between surfaces) on the optical axis between the first lens 1 and the second lens 2 as L_{12} , the ratio of it to the focal length f_0 of the overall projection lens system relates to the light amount in the middle field of the screen and the following relation is held as shown in Table 16.

$$(L_{12}/f_0) < 0.25$$

Beyond this range, the light amount ratio of the middle field of the screen area is reduced.

The ratio of the distance (axial distance between surfaces) L_{12} on the optical axis between the first lens 1 and the second lens 2 to the distance (axial distance between surfaces) L_{23} on the optical axis between the second lens 2 and the third lens 3 is decided by the balance of correction of aberration and the following relation is held as shown in Table 16.

$$(L_{12}/L_{23}) > 1.3$$

Below this range, no satisfactory focus performance can be obtained.

Between the absolute value of radius of curvature R_{a3} of the lens surface S_5 of the third lens 3 on the

screen side and the absolute value of radius of curvature Rb3 of the lens surface S6 of the third lens 3 on the image generating source side, the following relation is held:

5 $|Ra3| < |Rb3|$

The reason is that the spherical aberration and coma aberration caused by the third lens 3 are reduced.

Between the absolute value of radius of curvature Ra4 of the lens surface S7 of the fourth lens 4 on the
10 screen side and the absolute value of radius of curvature Rb4 of the lens surface S8 of the fourth lens 4 on the image generating source side, the following relation is held:

$$|Ra4| < |Rb4|$$

15 The reason is that the reduction in the share of the positive refractive power to the third lens 3 and the correction of chromatic aberration and spherical aberration are balanced. When a material of an Abbe's number of 45 or less is used for the fourth lens 4,
20 the chromatic aberration can be reduced.

The characteristics of the profile of lens surface are mentioned above on the basis of the lens data of the projection lens system in the embodiments of the present invention.

25 In this embodiment, the aspherical surfaces using

up to the aspherical coefficient of 10th order AH are described. Needless to say, a constitution that a coefficient of 12th order or higher is included is also included in the present invention.

5

Table 12

10

15

Lens No.	Lens surface S_1			Effective radius of surface S_1 (mm)
	As (mm)	Ss (mm)	As/Ss	
1	6.861	19.164	0.358	56.0
2	8.846	18.227	0.485	52.7
3	2.023	15.968	0.127	56.0
4	6.381	17.763	0.359	52.7
5	0.773	14.855	0.052	56.0
6	-0.402	14.460	-0.028	56.0
7	-0.693	14.620	-0.047	56.0
8	1.801	15.176	0.119	56.0
9	2.397	15.358	0.156	56.0
10	1.074	15.286	0.070	56.0

As: Aspherical surface sag amount (mm)
Ss: Spherical surface sag amount (mm)

20

25

Table 13

5

10

Lens No.	Lens surface S_8			Effective radius of surface S_8 (mm)
	As (mm)	Ss (mm)	As/Ss	
1	-2.759	-2.461	1.121	47.0
2	-2.386	-1.781	1.340	40.0
3	-2.239	-1.781	1.257	40.0
4	-2.950	-1.781	1.656	40.0
5	-5.032	-1.781	2.825	40.0
6	-3.409	0.161	-21.18	40.1
7	-3.376	0.201	-16.80	40.1
8	-4.202	-1.781	2.359	40.0
9	-2.657	-1.781	1.492	40.0
10	-4.196	-1.781	2.356	40.0

As: Aspherical surface sag amount (mm)
Ss: Spherical surface sag amount (mm)

Table 14

15

20

Lens No.	Lens surface S_{10}			Effective radius of surface S_{10} (mm)
	As (mm)	Ss (mm)	As/Ss	
1	2.389	-3.955	-0.604	42.0
2	2.621	-3.340	-0.785	40.0
3	5.613	-1.386	-4.050	40.0
4	2.621	-3.340	-0.785	40.0
5	4.994	-2.005	-2.491	40.0
6	3.675	-2.151	-1.709	38.0
7	3.721	-2.105	-1.767	38.0
8	4.994	-2.005	-2.491	40.0
9	4.994	-2.005	-2.491	40.0
10	4.994	-2.005	-2.491	40.0

25

As: Aspherical surface sag amount (mm)
Ss: Spherical surface sag amount (mm)

Table 15

Lens No.	Lens surface S_{11}			Effective radius of surface S_{11} (mm)
	As (mm)	Ss (mm)	As/Ss	
1	-20.744	-19.534	1.062	42.5
2	-18.823	-17.856	1.054	41.0
3	-18.330	-18.094	1.013	41.0
4	-21.605	-19.850	1.088	41.0
5	-19.314	-18.094	1.067	41.0
6	-17.858	-18.524	0.964	41.0
7	-17.680	-18.650	0.948	41.0
8	-19.111	-18.094	1.056	41.0
9	-19.132	-18.094	1.057	41.0
10	-19.542	-18.094	1.080	41.0

As: Aspherical surface sag amount (mm)
Ss: Spherical surface sag amount (mm)

Table 16

Lens No.	Focal length f_0 (mm)	Axial distance between lenses		L_{12}/L_{23}	L_{12}/f_0
		L_{12} (mm)	L_{23} (mm)		
1	90.486	15.473	8.707	1.777	0.171
2	90.310	20.146	4.933	4.084	0.223
3	90.775	18.075	9.167	1.972	0.199
4	89.473	13.907	10.482	1.327	0.155
5	90.130	17.286	8.149	2.121	0.192
6	90.276	17.162	5.811	2.954	0.190
7	90.339	17.162	5.079	3.379	0.190
8	90.098	17.431	7.842	2.223	0.194
9	90.330	16.778	10.013	1.676	0.186
10	90.277	16.478	8.988	1.833	0.183

L_{12} : Axial distance between first lens group and second lens group
 L_{23} : Axial distance between second lens group and third lens group
 f_0 : Focal length of overall projection lens system

Next, a method that in the projection lens system of the present invention, at least one communicating opening or communicating window extending outside of the projection lens system from the spaces between the lens elements is installed and that even if the heat quantity generated from the image generating source is large, the air temperature in the sealed space inside the lens barrel and the temperature of the lens elements are prevented from rising will be explained.

Fig. 20 is a cross sectional view showing the essential section of an example of a projection lens system of the prior art.

In Fig. 20, numeral 17 indicates a projection lens system, 8 a projection type cathode ray tube as an image generating source, 7 a liquid coolant, 20 lens elements, 9 a lens barrel as a lens element holding member, 11 a bracket as a connection member, and 10 elastic bodies. The lens barrel 9 has an inner barrel 9a and an outer barrel 9b and the lens elements 20 except the lens element 20a which is closest to the projection type cathode ray tube 8 are held in the inner barrel 9a with high precision. Both the lens element 20a and the projection type cathode ray tube 8 are pressed and held by the bracket 11 by a suitable holding means via the elastic bodies 10 and the liquid

coolant 7 is sealed in the space surrounded by the lens element 20a, the projection type cathode ray tube 8, and the bracket 11. At this time, the inside of the lens barrel 9 is a sealed structure practically. As a result, by the heat generated by the projection type cathode ray tube 8 which is an image generating source, the lens element 20a closest to the projection type cathode ray tube 8 and the air in the space between the lens element 20a and the lens element 20b second closest to the projection type cathode ray tube 8 are heated sequentially and furthermore, the temperature of the overall lens elements 20 and the air temperature in the sealed spaces between the lens elements rise gradually. This heat is radiated outside the projection lens system 17 almost only by heat transfer from the outer surface of the bracket 11, the outer surface of the lens barrel 9, and the outer surface of the lens element farthest away from the projection type cathode ray tube 8 among the lens elements 20. However, the material of lens elements is generally glass or plastics and when the lens barrel 9 is made of plastics from the point of view of moldability, the heat transfer coefficient from these outer surfaces is smaller than the heat transfer coefficient from the metal surface, so that the heat

radiation amount is smaller than the exothermic amount of the projection type cathode ray tube 8 and others and the air temperature in the sealed spaces and the temperature of the lens elements rise furthermore. As
5 a result, a problem arises that the heated lens elements are expanded or deformed and hence the focus performance of the projection lens system is extremely lowered. Therefore, it is a subject for design to suppress rising of the air temperature in the sealed
10 space in the lens barrel and the temperature of the lens elements and to prevent the lens elements from expansion and deformation even if the heat quantity from the image generating source is large.

Fig. 21 is a cross sectional view showing the
15 essential section of the 11th embodiment of the projection lens system 17 of the present invention and the same numeral is assigned to the part which is equivalent to a part shown in Fig. 20. The lens barrel 9 has an inner barrel 9a and an outer barrel 9b
20 holding the inner barrel 9a in the slidable state and the lens elements 20 except the lens element 20a which is closest to the projection type cathode ray tube 8 are held in the inner barrel 9a with high precision.

In Fig. 21, in the outer barrel 9b of the lens
25 barrel 9, at least one communicating opening (a

communicating window when the overall length of the opening is short) 27 for connecting the inside of the lens barrel 9 and the outside of the projection lens system is installed.

5 Fig. 22 is a cross sectional view showing the essential section when the cross section of the lens barrel 9 of the projection lens system 17 shown in Fig. 21 is seen in the direction of the arrow A. The inner barrel 9a is fitted and held by a plurality of fitting
10 protrusions 25 installed on the inner surface of the outer barrel 9b and grooves 28a between the fitting protrusions 25 become a second communicating opening 28. In Fig. 22, the fitting protrusions 25 on the inner surface side of the outer barrel 9b are
15 structured so that they are arranged at four locations on a cross section perpendicular to the optical axis. However, the present invention is not limited to this constitution. For example, the number of arrangement locations of the fitting protrusions 25 may be 3 or
20 any other number. These fitting protrusions 25 may be in a shape that they are cut into pieces in the direction of the optical axis and any constitution that the inner barrel 9a can slide inside the outer barrel 9b smoothly and that the grooves 28a can
25 fulfill the function as a communicating opening fully

is acceptable.

In this constitution, when the projection lens system is actually used, for example, when it is incorporated and used in a rear projection type image display apparatus, the right side (the projection type cathode ray tube side) of Fig. 21 is generally located low and the left side (the lens element side) is generally located up, so that the location of the second communicating opening 28 is generally higher than the location of the first communicating opening 27. Therefore, low-temperature air C (open air) introduced from the first communicating opening 27 is heated by the projection type cathode ray tube 8 in the space between the lens element 20a closest to the projection type cathode ray tube 8 and the lens element 20b second closest to it, and the temperature thereof rises, and the air becomes light due to volume expansion. Air H which is heated and lightened flows out of the second communicating opening 28. The lens elements 20 radiate heat efficiently by repetition of this series of phenomena, so that the expansion and deformation thereof can be suppressed and the focus performance of the projection lens system can be prevented from lowering.

Fig. 23 is a cross sectional view showing the

essential section of the 12th embodiment of the
projection lens system of the present invention, and
the same numeral is assigned to the part which is
equivalent to a part shown in Fig. 21, and explanation
5 is omitted.

Although the first communicating opening is
installed in the outer barrel 9b of the lens barrel 9
in the aforementioned 11th embodiment, the 12th
embodiment, as shown in Fig. 23, has a constitution
10 that junction protrusions 26 are installed, for
example, at three locations on one of the outer barrel
9b and the bracket 11 or both of them, and the outer
barrel 9b and the bracket 11 are joined at the
junction protrusions 26, and a gap portion 27a is
15 provided in the portion other than the junction
protrusions 26. Therefore, this gap portion 27a
functions as the first communicating opening 27
connected from the spaces between the lens elements to
the outside of the projection lens system.

20 Fig. 24 is a perspective view of the essential
section showing the actual constitution of the first
communicating opening 27 shown in Fig. 23. In Fig. 24,
the junction protrusions 26 are installed at three
locations on the end face of the bracket 11 and the
25 gap portion 27a between the junction protrusions 26 is

the first communicating opening 27. The junction
protrusions 26 may be installed on the flange surface
at the end of the outer barrel 9b instead of the end
face of the bracket 11 or may be installed on both of
5 them and put opposite to each other free of
substantial difference. In either case, the same
effect as that in the 11th embodiment can be obtained.

Fig. 25 is a cross sectional view showing the
essential section of the 13th embodiment of the
10 projection lens system of the present invention, and
the same numeral is assigned to the part which is
equivalent to a part shown in Figs. 21 and 23, and
explanation is omitted.

A difference of the 13th embodiment from the 12th
15 embodiment is a point that in the opening portions of
the first communicating opening 27 and the second
communicating opening 28 toward the outside of the
projection lens system, a first flange 29 and a second
flange 30 are arranged as a dust-proof member
20 respectively. In this case, assuming the communicating
openings including portions along the dust-proof
members 29 and 30 as a communicating opening
respectively, the shape of each communicating opening
itself can be regarded as a bent shape. In this
25 embodiment, in addition to the effects obtained in the

11th and 12th embodiments, since the system has a function for preventing a foreign material and light from entering the projection lens system and light leakage from the projection lens system, the contrast performance of the projection lens system itself will not be lowered and the image contrast of a rear projection type image display apparatus using the projection lens system will neither be lowered. Even if a curved shape or twisted shape is used as a shape of communicating opening in addition to the bent shape, the same effect can be obtained.

Fig. 26 is a cross sectional view showing the essential section of the 14th embodiment of the projection lens system of the present invention, and the same numeral is assigned to the part which is equivalent to a part shown in Figs. 21, 23, and 25, and explanation is omitted.

A difference of the 14th embodiment from the 11th embodiment is a point that the lens barrel 9 is of an integrated type that it is not separated into an outer barrel and an inner barrel. In this embodiment, the second communicating opening 28 is formed as a through hole inside the wall surface of the lens barrel 9. Even if this constitution is used, the same effect as that in the 11th and 12th embodiments can be obtained.

In the same way as with the 13th embodiment, when a dust-proof member (not shown in the drawing) is installed in the opening portion of the communicating opening toward the outside of the projection lens system, the same effect as that in the 13th embodiment is obtained.

Fig. 27 is a cross sectional view showing the essential section of the 15th embodiment of the projection lens system of the present invention, and the same numeral is assigned to the part which is equivalent to a part shown in Figs. 21, 23, 25, and 26, and explanation is omitted. A difference of the 15th embodiment from the 14th embodiment is a point that the second communicating opening 28 is formed as a through hole in the neighborhood of the periphery of each lens element instead of a through hole inside the wall surface of the lens barrel 9. Even if this constitution is used, the same effect as that in the 11th, 12th, and 14th embodiments can be obtained. In the same way as with the 13th embodiment, when a dust-proof member (not shown in the drawing) is installed in the opening portion of the communicating opening toward the outside of the projection lens system, the same effect as that in the 13th embodiment is obtained.

Next, the constitution when the projection lens

system as explained in each aforementioned embodiment is used in a projection type image display apparatus will be explained.

Fig. 28 is a cross sectional view showing the
5 essential section of the longitudinal cross section of a rear projection type image display apparatus using the projection lens system 17 of the present invention. Numeral 15 indicates a reflecting mirror, 16 a transmission type screen, 21 a cabinet, and 22 a
10 projection lens system holding member. The inside of the cabinet 21 is partitioned into an upper space 23 and a lower space 24 by the projection lens system holding member 22. The same numeral is assigned to the part which is equivalent to a part shown in each of
15 Figs. 21 to 27, and explanation is omitted.

In the rear projection type image display apparatus shown in Fig. 28, the aforementioned projection lens system 17 is held by the projection lens system holding member 22 and the lens barrel 9, each lens element therein, and the bracket 11 are
20 arranged in the upper space 23 in the cabinet. An original image displayed on the projection type cathode ray tube 8 which is an image generating source is enlarged by the projection lens system 17, and the
25 optical path thereof is folded by the reflecting

mirror 15, and the enlarged image is projected on the transmission type screen 16.

When the projection lens system according to the lens data shown in Tables 1 to 10 which is explained previously is used as a projection lens system, a compact set can be realized as the rear projection type image display apparatus shown in Fig. 28.

Fig. 29 is a cross sectional view showing the longitudinal cross section of a rear projection type image display apparatus when the rear projection type image display apparatus shown in Fig. 28 is structured so as to stand on end as another embodiment of a rear projection type image display apparatus using the projection lens system 17 of the present invention. Numerals 23' and 24' indicate an upper space and a lower space in the cabinet 21 respectively. The same numeral is assigned to the part which is equivalent to a part shown in Fig. 28.

Fig. 30 is a cross sectional view showing the projection lens system 17 of the rear projection type image display apparatus shown in Fig. 28 in detail.

Fig. 31 is a cross sectional view showing the projection lens system 17 of the rear projection type image display apparatus shown in Fig. 29 in detail.

The projection lens system 17 shown in Figs. 30

and 31 has a constitution equivalent to that of the 14th embodiment of the aforementioned projection lens system 17.

5 In the projection lens system 17 shown in Fig. 30, by the heat generated by the projection type cathode ray tube 8 which is an image generating source, the lens element 20a closest to the projection type cathode ray tube 8 and the air in the space between the lens element 20a and the lens element 20b second
10 closest to the projection type cathode ray tube 8 are heated sequentially, and the heated air H at high temperature flows out from the second communicating opening 28 formed in the lens barrel 9 into the upper space 23, and on the other hand, low-temperature air
15 (open air) C flows in from the first communicating opening 27. Also in the projection lens system 17 shown in Fig. 31, by the heat generated by the projection type cathode ray tube 8, the lens element 20a closest to the projection type cathode ray tube 8 and the air in the space between the lens element 20a
20 and the lens element 20b second closest to the projection type cathode ray tube 8 are heated sequentially, and the heated air H at high temperature flows out from the first communicating opening 27 into
25 the lower space 24', and on the other hand, low-

temperature air (open air) C flows in from the second communicating opening 28 formed in the lens barrel 9. By these operations, the efficiency of heat radiation from the lens elements increases, and the lens
5 elements 20a and 20b are prevented from rising of temperature, and expansion and heat deformation are generated little, and the focus performance as a projection lens system is prevented from changing due to temperature.

10 The projection lens system 17 shown in Figs. 30 and 31 may have the constitution shown in another embodiment of the projection lens system 17 and the same effect as that in the aforementioned case can be obtained. Furthermore, as shown in the 13th embodiment,
15 when a dust-proof member (not shown in the drawing) is installed in the opening portion of each communicating opening toward the outside of the projection lens system, since the projection lens system 17 has a function for preventing a foreign material and light
20 from entering the projection lens system and light leakage from the projection lens system, the image contrast of the rear projection type image display apparatus will not be lowered.

In the above description, the constitution that
25 each communicating opening is arranged in the space

between the lens element closest to the image
generating source and the lens element second closest
to it is mainly explained. However, the location of
each communication opening to be arranged is not
5 limited to it. Even if it is arranged in a space
between other lens elements, the same effect can be
obtained though it is inferior slightly.

Only a case that the projection type cathode ray
tube is used as an image generating source is
10 explained. However, even if a constitution that a
liquid crystal panel is combined with the light source
is used, since the light source becomes a heat
generating source, the same effect as the
aforementioned can be obtained. Furthermore, as an
15 example of the projection type image display apparatus
using the projection lens system of the present
invention, a rear projection type image display
apparatus is explained. However, needless to say, even
a case of a front projection type image display
20 apparatus can obtain the same effect.

The present invention obtains many good results
indicated below.

(1) Since a constitution that no concave lens is
arranged on the screen side of the third lens having
25 almost all the positive refractive power of the

overall projection lens system is used, even if the field angle is widened, distortion and astigmatism can be corrected and a high focus and a wide field angle are compatible with each other.

5 (2) Since a constitution that no concave lens is arranged between the third lens having the positive refractive power and the first lens closest to the screen side is used, the light focused in the marginal area is not diverged between them. As a result, the
10 height of light can be lowered and a good marginal light amount ratio can be realized.

 (3) Almost all the positive refractive power of the overall projection lens system is shared by the third lens and by combination of local aspherical
15 surface profiles of the first and second lenses, the lowering of the focus performance due to changes in temperature and absorption of moisture can be reduced.

 (4) When a lens having negative refractive power with the concave surface facing the screen side is
20 installed in the location closest to the projection tube which is an image light source as a sixth lens and the lens surface of the lens on the screen side is formed as a profile that the lens refractive power in the area through which the light flux from an object
25 in the marginal area on the fluorescent face passes is

weaker than that in the neighborhood of the optical axis of the lens, the difference in length of optical path between the saggital plane and the meridional plane is made smaller. Furthermore, in a lens arranged
5 next on the screen side to the above-mentioned lens having negative refractive power, when the profile of the lens surface on the projection tube side is convex on the projection tube side in the neighborhood of the optical axis and concave on the projection tube side
10 in the marginal area, the above difference in length of optical path can be made more smaller and the astigmatism in the marginal area can be corrected with higher precision.

(5) The third lens is an inexpensive low
15 dispersion glass convex lens and the cost of the overall projection lens system is reduced. To correct chromatic aberration, the fourth lens is a high dispersion plastic concave lens and used in combination with the third lens. Furthermore, a filter
20 for cutting the spurious component other than the dominant wavelength component of the light emission spectrum of a phosphorescent substance is installed in at least one lens of the lenses constituting the projection lens system and the generated chromatic
25 aberration itself is reduced.

(6) Furthermore, to realize a large aperture, the
aforementioned fourth lens is a large dispersion
plastic concave lens, and the profile thereof is
formed in a profile of strong aspherical surface, and
5 the aberration can be corrected with high precision.

The entry height of the upper ray into the third
lens (glass lens) can be lowered by the aspherical
surface profile of the fourth lens, so that the
diameter of the third lens (glass lens) can be
10 decreased for the same F-number and the cost can be
reduced.

Furthermore, the incident angle of the upper ray
into the third lens (glass lens) can be increased, so
that the refractive power of the third lens 3 can be
15 made smaller. As a result, an inexpensive glass
material with a refractive index n_d of 1.6 or less can
be used and the cost can be reduced.

When the aforementioned projection lens system is
used, a bright and high focus image can be obtained in
20 the overall area of the screen and a compact
projection type display apparatus can be realized.
When the projection lens system of the present
invention is applied, between the distance (projection
distance) L (mm) from the top of the lens surface of
25 the lens closest to the screen in the first lens on

the screen side to the transmission type screen and the diagonal effective size M (inch) of the transmission type screen, the following relation is held:

5 $17.3 < (L/M) < 17.6$

and a compact set can be realized.

On the other hand, according to the present invention, when the communicating opening or communicating window explained in each aforementioned embodiment is arranged in the lens barrel of the projection lens system or others, the efficiency of heat radiation from the lens elements is increased by the convection action of air, and the lens elements are suppressed in rising of temperature, and the expansion and deformation due to rising of temperature are suppressed, and as a result, the lens performance, particularly the focus performance are prevented from lowering.

Furthermore, when a dust-proof member in a shape such as a flange is arranged in a suitable location of the opening portion of the aforementioned communicating opening or communicating window toward the outside of the projection lens system or when the communicating opening or communicating window itself is formed in a bent, or curved, or twisted shape,

entry of a foreign material or light into the projection lens system and light leakage from the inside of the projection lens system are prevented, and the contrast performance of the projection lens system itself will not be lowered, and the image contrast of a projection type image display apparatus using the projection lens system will be neither reduced.